

UV FLOORVINYL

Product Information

Produktinformation

Productinformatie

Wear Classification	Strapazierwert	Slijtage Classificatie	EN ISO 108744 EN 685		22 Domestic 22 Privatbereich 22 Huishoudelijk
Wear Layer	Stärke der Nutzschrift	Slijtlaag	EN ISO 24340 EN 4291		0,20 mm
Total Thickness	Gesamtdicke	Totale Dikte	EN ISO 24346 EN 428		2,00 mm
Total Weight	Gesamtgewicht	Totaalgewicht	EN ISO 23997 EN 430		1250 gr/m ²
Standard Width	Standard Breite	Standard Breedte	EN ISO 24341 EN 426		200,5 cm
Standard Length	Standard Länge	Standard Lengte	EN ISO 24341 EN 426		25 m

Technical Information

Technische Daten

Technische Informatie

Dimensional Stability	Maßstabilität	Maatstablieit	EN ISO 23999 EN434		≤0,40%
Underfloor Heating	Fußbodenheizung	Vloerverwarming	EN 12667		Suitable / Geeignet / Geschikt
Residual Indentation	Resteindruck	Restindruk	EN ISO 24343-2 EN 433		< 0,35 mm
Reaction to Fire	Brennverhalten	Brandklasse	EN 13501-1		Bfl / S1
Slip Resistance	Aintrutsch	Antislip	DIN 51130		R10
Dynamic Coefficient of friction	Gleitwiderstand	Glijweerstand	EN 13893		> 0,6

We reserve the right to change above specs to improve quality. Wir behalten uns das Recht vor, Änderungen in Bezug auf Material und Konstruktion vorzunehmen, wenn es der Verbesserung der Qualität dient. We behouden ons het recht voor om bovengenoemde specificaties te wijzigen om de kwaliteit te verbeteren.